

## Overview

The GCS- 0521 series hotel electronic locks adopt a fully-body design with an elegant appearance combined with superior lock performance.

With a wide range of mortise for options, the GCS-0521 can be used with a variety of standard and narrow door.



## FEATURES

Standalone electronic lock with RFID technology.

High security mortise lockcase with European standard.

CE, FCC approved.

Solid steel handles with self-lubricating long life bearings.

2-point steel latch construction with an anti-friction mechanism.

Panic release function – the deadbolt and latch are automatically retracted by inside handle for easy egress in emergency situations.

Long lasting Escutcheon and durable handle levers.

Lock programming and audit records are not erased during battery replacement.

Powered by four (4) AAA batteries that provide up to 12-18 months normal life.

Up to 990 event audit trail.

Low battery indicator alerts staff.

High security concealed cylinder override.

Customize key cards for different levels of access authorization.

Opening error detected by LED light and beep sound.

All cards have an effective period. Guest cards have limited access functions and expiration date.

Staff cards can be preset for operation during specified time and day.

Material	5# Zinc alloy, 304# stainless steel, ABS
Metal finishes	Stainless steel brush
Battery location	Inside of the room
Power	6V DC 4 × AAA alkaline batter-
Low Battery Indicator	Alerts staff that batteries need to be changed soon
Emergency Opening Option	Mechanical metal Key
User interface	2 colored LED display (blue and red)
Locking mechanism	Electro-mechanical locking mechanism located in the lockcase.
Mortise option	European 4085 4585, 6085 mortise for options.
Working Temperature	-25°C-60°C
Working Humidity	10%-85%
Audit Trail	990 latest records include mechanical key
Door Thickness	40-70mm
Certifications	China Ministry of Public Security (MA) European CE-RED Directives USA FCC Part 15C (FCC ID) Australia C-Tick AS/NZS 4268

